

Size	Orientation	Pins	Core	M / F	LED
M8	Straight	3	3	Female	-
M8	Right Angled	3	3	Female	-
M8	Straight	4	4	Female	-
M8	Right Angled	4	4	Female	-
M8	Straight	3	3	Male	-
M8	Straight	4	4	Male	-

Size	Orientation	Pins	Core	M / F	LED
M12	Straight	4	3 / 4	Female	-
M12	Right Angled	4	3 / 4	Female	-
M12	Right Angled	4	3 / 4	Female	2 / 3
M12	Straight	5	5	Female	-
M12	Right Angled	5	5	Female	-
M12	Straight	8	8	Female	-
M12	Straight	4	3	Male	-
M12	Straight	4	4	Male	-
M12	Straight	5	5	Male	-
M12	Straight	8	8	Male	-

Design and specifications subject to change without prior notice

- ✓ Sheath color identifications comply with European Standards
- ✓ Cable socket, with integrally moulded lead, self-securing lock nut
- ✓ Screw locking, metal coupling nut and self-assembly
- ✓ Connector assembly also available without cable
- ✓ All combinations also available with shielded type cable

Common Specifications

- ✓ Rated Operating Voltage : 60 V DC
- ✓ Current Rating : 3A at +25 deg C
- ✓ Insulation Resistance : ≥ 100 Mega Ohm
- ✓ Temperature Range : - 25 ... +75 deg C
- ✓ Grip Material : PU
- ✓ Contact : Cu-Zn
- ✓ Contact Carrier : Nylon 66
- ✓ O-Ring : Neoprene
- ✓ Grip Colour : Black
- ✓ Cable Sheath Colour : Black
- ✓ Cross Section of Wire : 0.25 sq. mm
- ✓ Core Diameter : 1.25 mm
- ✓ Termination : Partially Stripped



Pictures for illustration only.

Cable : PVC / PUR

Standard Length : 2 / 3 / 5 / 7 / 10 m
(any cable length can be provided)

Other customized combinations also available